

SA5.0 THRU SA170A


Features

- *500W Peak pulse power capability
- *Excellent clamping capability
- *Low incremental surge resistance
- *Fast response time: Typically less than 1.0ps from 0v to VBR for unidirectional and 5.0 ns for bidirectional types.

Mechanical Data

- *Cases: Molded plastic
- *Epoxy: UL94V-0 rate flame retardant
- *Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- *Polarity: Color band denotes cathode except Bipolar
- *Mounting position: Any
- *Weight: 0.40 gram

DO-15



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

Type Number		Value	Units
Peak Power Dissipation (Note 1)	PPPM	Minimum 500	W
Peak Pulse reverse current (Note 1)	IPPM	See Table	A
Steady State Power Dissipation (Note 2)	PM(AV)	1.0	W
Peak Forward Surge Current (Note 3)	IFSM	70	A
Maximum Instaneous Forward Voltage at 50.0A for Unidirectional Only	V _F	3.5	V
Operating and Storage Temperature Range	T _J , T _{STG}	-55~+175	°C

- NOTES: 1. 10/100us waveform Non-repetitive Current Pulse Per Fig.3 and Derated above TA=25°C Per Fig.2.
2. T1=75°C, lead lengths 9.5mm. Mounted on Copper Pad Area of (40 x40 mm) Fig.5
3. Measured on 8.3ms Single Half Sine-Wave or Equivalent Square Wave, Duty Cycle=4 Pulses Per Minute Maximun.
Devices for Bipolar Applications
1. For Bidirectional Use C or CA Suffix for Types SA5.0 thru types SA170 (e.g.SA5.0C,SA170CA)
2. Electrical Characteristics Apply in Both Directions.

RATING AND CHARACTERISTIC CURVES SA5.0 THRU SA170A

FIG.1- PEAK PULSE POWER RATING CURVE




FIG.2-PULSE DERATING CURVE




FIG.3- PULSE WAVEFORM




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT UNIDIRECTIONAL ONLY





FIG.5-STEADY STATE POWER DERATING CURVE



ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Device Type	Breakdown Voltage		Test Current	Start-off voltage	Maximun Reverse Leakage at VWM	Maximun Peak Pulse Current	Maximun Clamping Voltage at IPPM	Maximun Temperature Coefficient of VBR
	V(BR) (Note1)		I _T	VWM	I _D (Note3)	IPPM(Note2)	V _c	
	Volts		(mA)	(Volts)	uA	Amps	Volts	
	Min	Max						
SA5.0	6.40	7.30	10.0	5.0	600	54.0	9.60	5.0
SA5.0A	6.40	7.00	10.0	5.0	600	57.0	9.20	5.0
SA6.0	6.67	8.15	10.0	6.0	600	46.0	11.4	5.0
SA6.0A	6.67	7.37	10.0	6.0	600	50.0	10.3	5.0
SA6.5	7.22	8.82	10.0	6.5	400	42.0	12.3	5.0
SA6.5A	7.22	7.98	10.0	6.5	400	46.0	11.2	5.0
SA7.0	7.78	9.51	1.0	7.0	150	39.0	13.3	6.0
SA7.0A	7.78	8.60	1.0	7.0	150	43.0	12.0	6.0
SA7.5	8.33	10.2	1.0	7.5	50	36.0	14.3	7.0
SA7.5A	8.33	9.21	1.0	7.5	50	40.0	12.9	7.0
SA8.0	8.89	10.9	1.0	8.0	25	35.0	15.0	7.0
SA8.0A	8.89	9.83	1.0	8.0	25	38.0	13.6	7.0
SA8.5	9.44	11.5	1.0	8.5	10	33.0	15.9	8.0
SA8.5A	9.44	10.4	1.0	8.5	10	36.0	14.4	8.0
SA9.0	10.0	12.2	1.0	9.0	5.0	31.0	16.9	9.0
SA9.0A	10.0	11.1	1.0	9.0	5.0	34.0	15.4	9.0
SA10	11.1	13.6	1.0	10.0	1.0	27.0	18.8	10.0
SA10A	11.1	12.3	1.0	10.0	1.0	30.0	17.0	10.0
SA11	12.2	14.9	1.0	11.0	1.0	26.0	20.1	11.0
SA11A	12.2	13.5	1.0	11.0	1.0	28.0	18.2	11.0
SA12	13.3	16.3	1.0	12.0	1.0	23.0	22.0	12.0
SA12A	13.3	14.7	1.0	12.0	1.0	26.0	19.9	12.0
SA13	14.4	17.6	1.0	13.0	1.0	22.0	23.8	13.0
SA13A	14.4	15.9	1.0	13.0	1.0	24.0	21.5	13.0
SA14	15.6	19.1	1.0	14.0	1.0	20.3	25.8	14.0
SA14A	15.6	17.2	1.0	14.0	1.0	22.6	23.2	14.0
SA15	16.7	20.4	1.0	15.0	1.0	19.5	26.9	16.0
SA15A	16.7	18.5	1.0	15.0	1.0	21.0	24.4	16.0
SA16	17.8	21.8	1.0	16.0	1.0	18.0	28.8	19.0
SA16A	17.8	19.7	1.0	16.0	1.0	20.0	26.0	17.0
SA17	18.9	23.1	1.0	17.0	1.0	17.0	30.5	20.0
SA17A	18.9	20.9	1.0	17.0	1.0	19.0	27.6	19.0
SA18	20.0	24.4	1.0	18.0	1.0	16.3	32.2	21.0
SA18A	20.0	22.1	1.0	18.0	1.0	17.9	29.2	20.0
SA20	22.2	27.1	1.0	20.0	1.0	14.0	35.8	25.0
SA20A	22.2	24.5	1.0	20.0	1.0	16.0	32.4	23.0
SA22	24.4	29.8	1.0	22.0	1.0	13.0	39.4	28.0
SA22A	24.4	26.9	1.0	22.0	1.0	14.7	35.6	25.0
SA24	26.7	32.6	1.0	24.0	1.0	12.0	43.0	31.0
SA24A	26.7	29.5	1.0	24.0	1.0	13.4	38.9	28.0
SA26	28.9	35.3	1.0	26.0	1.0	11.0	46.6	31.0
SA26A	28.9	31.6	1.0	26.0	1.0	12.4	42.1	30.0
SA28	31.1	38.0	1.0	28.0	1.0	10.0	50.1	35.0
SA28A	31.1	34.4	1.0	28.0	1.0	11.5	45.4	31.0
SA30	33.3	40.7	1.0	30.0	1.0	9.8	53.5	39.0
SA30A	33.3	36.8	1.0	30.0	1.0	10.8	48.4	36.0
SA33	36.7	44.9	1.0	33.0	1.0	8.8	59.0	42.0
SA33A	36.7	40.6	1.0	33.0	1.0	9.8	53.3	39.0

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Device Type	Breakdown Voltage		Test Current	Stand-off voltage	Maximun Reverse Leakage at VWM	Maximun Peak Pulse Current	Maximun Clamping Voltage at IPPM	Maximun Temperature Coefficient of VBR
	V(BR) (Note1)		IT	VWM	ID(Note3)	IPPM(Note2)	Vc	
	Volts		(mA)	(Volts)	uA	Amps	Volts	
	Min	Max						
SA36	40.0	48.9	1.0	36.0	1.0	8.1	64.3	46.0
SA36A	40.0	44.2	1.0	36.0	1.0	9.0	58.1	41.0
SA40	44.4	54.3	1.0	40.0	1.0	7.3	71.4	51.0
SA40A	44.4	49.1	1.0	40.0	1.0	8.1	64.5	46.0
SA43	47.8	58.4	1.0	43.0	1.0	6.8	76.7	55.0
SA43A	47.8	52.8	1.0	43.0	1.0	7.5	69.4	50.0
SA45	50.0	61.1	1.0	45.0	150	6.5	80.3	58.0
SA45A	50.0	55.3	1.0	45.0	150	7.2	72.7	52.0
SA48	53.3	65.2	1.0	48.0	50	6.1	85.5	63.0
SA48A	53.3	58.9	1.0	48.0	50	6.7	77.4	56.0
SA51	56.7	69.3	1.0	51.0	25	5.7	91.1	66.0
SA51A	56.7	62.7	1.0	51.0	25	6.3	82.4	61.0
SA54	60.0	73.3	1.0	54.0	10	5.4	96.3	71.0
SA54A	60.0	66.3	1.0	54.0	10	6.0	87.1	65.0
SA58	64.4	78.7	1.0	58.0	5.0	5.0	103	78.0
SA58A	64.4	71.2	1.0	58.0	5.0	5.6	93.6	70.0
SA60	66.7	81.5	1.0	60.0	1.0	4.9	107	80.0
SA60A	66.7	73.7	1.0	60.0	1.0	5.4	96.8	71.0
SA64	71.1	86.9	1.0	64.0	1.0	4.6	114	86.0
SA64A	71.1	78.6	1.0	64.0	1.0	5.0	103	76.0
SA70	77.8	95.1	1.0	70.0	1.0	4.2	125	94.0
SA70A	77.8	86	1.0	70.0	1.0	4.6	113	85.0
SA75	88.3	102	1.0	75.0	1.0	3.9	134	101
SA75A	88.3	92.1	1.0	75.0	1.0	4.3	121	91
SA78	86.7	103	1.0	78.0	1.0	3.7	139	105
SA78A	86.7	95.8	1.0	78.0	1.0	4.1	126	95
SA85	94.4	115	1.0	85.0	1.0	3.4	151	114
SA85A	94.4	104	1.0	85.0	1.0	3.8	137	103
SA90	100	122	1.0	90.0	1.0	3.2	160	121
SA90A	100	111	1.0	90.0	1.0	3.5	146	110
SA100	111	136	1.0	100	1.0	2.9	179	135
SA100A	111	123	1.0	100	1.0	3.2	162	123
SA110	122	149	1.0	110	1.0	2.6	196	148
SA110A	122	135	1.0	110	1.0	2.9	177	133
SA120	133	163	1.0	120	1.0	2.4	214	162
SA120A	133	147	1.0	120	1.0	2.7	193	146
SA130	144	176	1.0	130	1.0	2.2	230	175
SA130A	144	159	1.0	130	1.0	2.5	209	158
SA150	167	204	1.0	150	1.0	1.9	268	203
SA150A	167	185	1.0	150	1.0	2.1	243	184
SA160	178	218	1.0	160	1.0	2.0	257	217
SA160A	178	197	1.0	160	1.0	2.0	259	196
SA170	189	231	1.0	170	1.0	1.7	304	230
SA170A	189	209	1.0	170	1.0	1.9	275	208

Notes:
 1.VBR measured after IT applied for 300us.IT=square wave pulse or equivalent.
 2.Surge current waveform per Figure 3 and derate per Figure 2.
 3.For bipolar types having VWMof 10 volts and under,the ID limit is doubled.
 4.All terms and symbols are consistent with ANSI/IEEE C62.35.