

SMCJ SERIES

SURFACE MOUNT TRANSIENT VOLTAGE SUPPRESSOR

Voltage Range
5.0 to 170 Volts
1500 Watts Peak Power


Features

- For surface mounted application
- Low profile package
- Built-in strain relief
- Glass passivated junction
- Fast response time: Typically less than 1.0ps from 0 volt to BV min.
- Typical Ir less than 1uA above 10V
- High temperature soldering guaranteed:
250°C/ 10 seconds at terminals
- Plastic material used carries Underwriters Laboratory Flammability Classification 94V-0
- 600 watts peak pulse power capability with a 10 x 1000 us waveform by 0.01% duty cycle

Mechanical Data

- Case: Molded plastic
- Terminals: Solder plated
- Polarity: Indicated by cathode band
- Standard Packaging: 16mm tape (EIA STD RS-481)
- Weight: 0.21 gram

SMC/DO-214AB



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Type Number		Value	Units
Peak Power Dissipation at $T_A=25^\circ\text{C}$, $T_p=1\text{ms}$ (Note 1)	PPK	Minimum 1500	Watts
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)(Note 2, 3)-Unidirectional Only	IFSM	100	Amps
Maximum Instantaneous Forward Voltage at 100.0A for Unidirectional Only(Note 4)	V _F	3.5/5.0	Volts
Operating and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

- NOTES: 1. Non-repetitive Current Pulse Per Fig.3 and Derated above $T_A=25^\circ\text{C}$ Per Fig.2.
 2. Mounted on 5.0mm² (.013 mm Thick) Copper Pads to Each Terminal.
 3. 8.3ms Single Half Sine-Wave or Equivalent Square Wave, Duty Cycle=4 Pulses Per Minutes Maximum.
 4. V_F=3.5V on SMCJ5.0 thru SMCJ90 Devices and V_F=5.0V on SMCJ100 thru SMCJ170 Devices.
 Devices for Bipolar Applications
 1. For Bidirectional Use C or CA Suffix for Types SMCJ5.0 through Types SMCJ170.
 2. Electrical Characteristics Apply in Both Directions.

RATING AND CHARACTERISTIC CURVES SMCJ SERIES

FIG.1- PEAK PULSE POWER RATING CURVE




FIG.2-PULSE DERATING CURVE




FIG.3-PULSE WAVEFORM




FIG.4-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.5-TYPICAL JUNCTION CAPACITANCE BIDIRECTIONAL





FIG.6-TYPICAL JUNCTION CAPACITANCE



ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Device Type Modified "J" Bend Lead	Device Marking Code	Breakdown Voltage V(BR) (Volts) (Note 1) (MIN / MAX)	Test Current at Ir(mA)	Stand-Off Voltage Vwm(Volts)	Maximun Reverse Leakage at Vwm (Note 3) Id (uA)	Maximun Peak Pulse Surge Current Ippm (Note 2)(Amps)	Maximun Clamping Voltage at Ippm Vc(Volts)
SMCJ5.0	GDD	6.40/7.3	10.0	5.0	1000	164.0	9.6
SMCJ5.0A	GDE	6.40/7.0	10.0	5.0	1000	171.0	9.2
SMCJ6.0	GDF	6.67/8.15	10.0	6.0	1000	138.0	11.4
SMCJ6.0A	GDG	6.67/7.37	10.0	6.0	1000	152.0	10.3
SMCJ6.5	GDH	7.22/8.82	10.0	6.5	500	128.0	12.3
SMCJ6.5A	GDK	7.22/7.98	10.0	6.5	500	140.0	11.2
SMCJ7.0	GDL	7.78/9.51	10.0	7.0	200	118.0	13.3
SMCJ7.0A	GDM	7.78/8.60	10.0	7.0	200	131.0	12.0
SMCJ7.5	GDN	8.33/10.3	1.0	7.5	100	110.0	14.3
SMCJ7.5A	GDP	8.33/9.21	1.0	7.5	100	122.0	12.9
SMCJ8.0	GDQ	8.89/10.9	1.0	8.0	50	105.0	15.0
SMCJ8.0A	GDR	8.89/9.83	1.0	8.0	50	115.0	13.6
SMCJ8.5	GDS	9.44/11.5	1.0	8.5	20	99.0	15.9
SMCJ8.5A	GDT	9.44/10.4	1.0	8.5	20	109.0	14.4
SMCJ9.0	GDU	10.0/12.2	1.0	9.0	10	93.0	16.9
SMCJ9.0A	GDV	10.0/11.1	1.0	9.0	10	102.0	15.4
SMCJ10	GDW	11.1/13.6	1.0	10.0	5.0	83.0	18.8
SMCJ10A	GDX	11.1/12.3	1.0	10.0	5.0	92.0	17.0
SMCJ11	GDY	12.2/14.9	1.0	11.0	5.0	78.0	20.1
SMCJ11A	GDZ	12.2/13.5	1.0	11.0	5.0	86.0	18.2
SMCJ12	GED	13.3/16.3	1.0	12.0	5.0	71.0	22.0
SMCJ12A	GEE	13.3/14.7	1.0	12.0	5.0	79.0	19.9
SMCJ13	GEF	14.4/17.6	1.0	13.0	5.0	66.0	23.8
SMCJ13A	GEG	14.4/15.9	1.0	13.0	5.0	73.0	21.5
SMCJ14	GEH	15.6/19.1	1.0	14.0	5.0	61.0	25.8
SMCJ14A	GEK	15.6/17.2	1.0	14.0	5.0	67.0	23.2
SMCJ15	GEL	16.7/20.4	1.0	15.0	5.0	58.0	26.96
SMCJ15A	GEM	16.7/18.5	1.0	15.0	5.0	64.0	24.4
SMCJ16	GEN	17.8/21.8	1.0	16.0	5.0	54.0	28.8
SMCJ16A	GEP	17.8/19.7	1.0	16.0	5.0	60.0	26.0
SMCJ17	GEQ	18.9/23.1	1.0	17.0	5.0	51.0	30.5
SMCJ17A	GER	18.9/20.9	1.0	17.0	5.0	57.0	27.6
SMCJ18	GES	20.0/24.4	1.0	18.0	5.0	48.0	32.2
SMCJ18A	GET	20.0/22.1	1.0	18.0	5.0	53.0	29.2
SMCJ20	GEU	22.2/27.1	1.0	20.0	5.0	43.0	35.8
SMCJ20A	GEV	22.2/24.5	1.0	20.0	5.0	48.0	32.4
SMCJ22	GEW	24.4/29.8	1.0	22.0	5.0	39.0	39.4
SMCJ22A	GEX	24.4/26.9	1.0	22.0	5.0	44.0	35.5
SMCJ24	GEY	26.7/32.6	1.0	24.0	5.0	36.0	43.0
SMCJ24A	GEZ	26.7/29.5	1.0	24.0	5.0	40.0	38.9
SMCJ26	GFD	28.9/35.3	1.0	26.0	5.0	33.0	46.6
SMCJ26A	GFE	28.9/31.9	1.0	26.0	5.0	37.0	42.1
SMCJ28	GFF	31.1/38.0	1.0	28.0	5.0	31.0	50.0
SMCJ28A	GFG	31.1/34.4	1.0	28.0	5.0	34.0	45.4
SMCJ30	GFH	33.3/40.7	1.0	30.0	5.0	29.0	53.5
SMCJ30A	GFK	33.3/36.8	1.0	30.0	5.0	32.0	48.4
SMCJ33	GFL	36.7/44.9	1.0	33.0	5.0	26.0	59.0
SMCJ33A	GFM	36.7/40.6	1.0	33.0	5.0	29.0	53.3
SMCJ36	GFN	40.0/48.9	1.0	36.0	5.0	24.0	64.3
SMCJ36A	GFP	40.0/44.2	1.0	36.0	5.0	27.0	58.1
SMCJ40	GFQ	44.4/54.3	1.0	40.0	5.0	22.0	71.4
SMCJ40A	GFR	44.4/49.1	1.0	40.0	5.0	24.0	64.5
SMCJ43	GFS	47.8/58.4	1.0	43.0	5.0	20.0	76.7
SMCJ43A	GFT	47.8/52.8	1.0	43.0	5.0	22.0	69.4

ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Device Type Modified "J" Bend Lead	Device Marking Code	Breakdown Voltage V(BR) (Volts) (Note 1) (MIN / MAX)	Test Current at It(mA)	Stand-Off Voltage Vwm(Volts)	Maximun Reverse Leakage at Vwm (Note 3) Id (uA)	Maximun Peak Pulse Surge Current Ippm (Note 2)(Amps)	Maximun Clamping Voltage at Ippm Vc(Volts)
SMCJ45	GFU	50.0/61.1	1.0	45.0	5.0	19.0	80.3
SMCJ45A	GFV	50.0/55.3	1.0	45.0	5.0	21.0	72.7
SMCJ48	GFW	53.3/65.1	1.0	48.0	5.0	18.0	85.5
SMCJ48A	GFY	53.3/58.9	1.0	48.0	5.0	20.0	77.4
SMCJ51	GFZ	56.7/69.3	1.0	51.0	5.0	17.0	91.1
SMCJ51A	GFZ	56.7/62.7	1.0	51.0	5.0	19.0	82.4
SMCJ54	GGD	60.0/73.3	1.0	54.0	5.0	16.0	96.3
SMCJ54A	GGE	60.0/66.3	1.0	54.0	5.0	18.0	87.1
SMCJ58	GGF	64.4/78.7	1.0	58.0	5.0	15.0	103.0
SMCJ58A	GGG	64.4/71.2	1.0	58.0	5.0	16.0	93.6
SMCJ60	GGH	66.7/81.5	1.0	60.0	5.0	14.0	107.0
SMCJ60A	GGK	66.7/73.7	1.0	60.0	5.0	16.0	96.8
SMCJ64	GGL	71.1/86.9	1.0	64.0	5.0	13.8	114.0
SMCJ64A	GGM	71.1/78.6	1.0	64.0	5.0	15.0	103.0
SMCJ70	GGN	77.8/95.1	1.0	70.0	5.0	12.6	125.0
SMCJ70A	GGP	77.8/86.0	1.0	70.0	5.0	13.9	113.0
SMCJ75	GGQ	83.3/102	1.0	75.0	5.0	11.7	134.0
SMCJ75A	GGR	83.3/92.1	1.0	75.0	5.0	13.0	121.0
SMCJ78	GGS	86.7/106	1.0	78.0	5.0	11.3	139.0
SMCJ78A	GGT	86.7/95.8	1.0	78.0	5.0	12.5	126.0
SMCJ85	GGU	94.4/115	1.0	85.0	5.0	10.4	151.0
SMCJ85A	GGV	94.4/104	1.0	85.0	5.0	11.5	137.0
SMCJ90	GGW	100/122	1.0	90.0	5.0	9.8	160.0
SMCJ90A	GGX	100/111	1.0	90.0	5.0	10.7	146.0
SMCJ100	GGY	111/136	1.0	100.0	5.0	8.8	179.0
SMCJ100A	GGZ	111/123	1.0	100.0	5.0	9.7	162.0
SMCJ110	GHD	122/149	1.0	110.0	5.0	8.0	196.0
SMCJ110A	GHE	122/135	1.0	110.0	5.0	8.9	177.0
SMCJ120	GHF	133/163	1.0	120.0	5.0	7.3	214.0
SMCJ120A	GHG	133/147	1.0	120.0	5.0	8.1	193.0
SMCJ130	GHH	144/176	1.0	130.0	5.0	6.8	231.0
SMCJ130A	GHK	144/159	1.0	130.0	5.0	7.5	209.0
SMCJ150	GHL	167/204	1.0	150.0	5.0	5.8	268.0
SMCJ150A	GHM	167/185	1.0	150.0	5.0	6.4	243.0
SMCJ160	GHN	178/218	1.0	160.0	5.0	5.4	287.0
SMCJ160A	GHP	178/197	1.0	160.0	5.0	6.0	259.0
SMCJ170	GHQ	189/231	1.0	170.0	5.0	5.1	304.0
SMCJ170A	GHR	189/209	1.0	170.0	5.0	5.7	275.0

Notes:

- 1.V(BR) measured after It applied for 300us,It=Square wave pulse or equivalent.
- 2.Surge current wave from per Fig.3 and derate per Figure 2.
- 3.For bidirectional types having Vwm of 10 Volts and less,the Id limit is doubled
- 4.all terms and symbols are consistent with ANSI/IEEE C62.35